

# PRIMER SPRAY


## UNIVERSAL SPRAY PRIMER FOR ACRYLIC ADHESIVE TAPES

### INSTANTANEOUS

Thanks to spray can application and the adjustable nozzle, no brushes or other equipment is needed for installation.

### HIGH PERFORMANCE

At a distance of approx. 30 - 50 cm from the surface approx. 6 cm of gluing area is achieved.  
Ideal for use with Rothoblaas tapes.



## TECHNICAL DATA

Properties	value	USC units
Composition	mix of thermoplastic adhesive and solvent	-
Time required for drying 20 °C/50 %RH	1-2 minutes	-
Application temperature (cartridge, ambient and support)	+15/+25°C	+59/+77 °F
Temperature resistance after drying	-10/+100°C	+14/+212 °F
French VOC classification	A+	-
Transport temperature	+5/+50°C	+41/+122 °F
Storage temperature <sup>(1)</sup>	+15/+35 °C	+59/+95 °F

<sup>(1)</sup>Store the product in a dry place and check the date of manufacture on the cartridge.

Waste classification (2014/955/EU): 16 05 04.  
Aerosol 1 - H222, H229.

## CODES AND DIMENSIONS

CODE	content [ml]	content [US fl oz]	
PRIMERSPRAY	750	25.36	12



### FAST INSTALLATION

It allows smoothing of even the roughest and most fibrous surfaces to facilitate the application of tapes or sealants.

### ADJUSTABLE

Adjustable nozzle for a more precise application adapted to each situation. Simply turn the nozzle to increase or decrease the spray area.