I SNAP



CONNECTOR AND SPACER FOR DECKS

VERSATILITY

It can be used both as a concealed connector for boards and as a spacer between boards and battens. SNAP is developed to be used individually but also in combination. In this case, SNAPs have dual functionality as connector and spacer, for maximum efficiency and convenience.

MICRO VENTILATION

When used as a spacer, SNAP prevents water stagnation thanks to the micro-ventilation created under the decking boards.


DURABILITY

PP (glass fiber reinforced polypropylene) material provides excellent durability at an affordable price.











FIELDS OF USE

Outdoor use.

Fastening of timber or WPC boards with symmetrical milling on substructures in wood, WPC or aluminium.

CODES AND DIMENSIONS

CODE	material	PxBxs		f	Ø	pcs
		[mm]	[in]	[in]	[in]	
SNAP	polypropylene	70 x 28 x 4	2.76 x 1.10 x 0.16	0.25	0.21	100


KKT COLOR

fastening on softwood



d_1	CODE	L		pcs
[mm] [in]		[mm]	[in]	
5 0.20	KKTN540(*)	43	1 11/16	200
#11 TX 20	KKTN550	53	2 1/16	200

^(*) Fully threaded screw.



KKZ A2 | AISI304

fastening on hardwood



d_1	CODE	L		pcs
[mm] [in]		[mm]	[in]	
5 0.20	KKZ550	50	1 15/16	200
#11 TX 20	KKZ560	60	2 3/8	200


KKZ EVO C5


fastening on hardwood



d_1	CODE	L		pcs
[mm] [in]		[mm]	[in]	
5 0.20	KKZEVO550C5	50	1 15/16	200
#11 TX 20	KKZEVO560C5	60	2 3/8	200

GEOMETRY







pcs

200


200



INSTALLATION







GROOVING				
Min. thickness	F	0.16 in		
Min. recommended height H	Н	0.28 in		



DECK KIT

SNAP, KKT screws, TERRA BAND UV tape and GRANULO or NAG batten supports constitute the most convenient combination of products for building a strong and durable terrace quickly and economically.